# **FIBERPAD**

## Refining mat

Structured, natural parquet surfaces are enjoying great popularity!

...we show you how it works.



The advantage for your customers: the treated surface has a higher quality and is less delicate

Prerequisites: factory pre-sanded parquet flooring or prepared/pre-sanded in situ

### Fine sanding with structural effect

...transforms every parquet flooring into a lively surface.

The FIBERPAD achieves through its shape and fibre structure a very high sanding performance, excellent dust extraction and finally a spotless and scratch-free surface, ready to be oiled or varnished.

Excellent results can be achieved with the Velcro backed FIBERPAD Ø150 together with the TRIVO-DISC and Columbus machine.

The FIBERPAD Ø150 is also perfectly suited for edge sanding and can be mounted onto most edge sanders.



Order-no. 488 811 000



at a glance: no scratches when sanding

The most important features

- steady sanding performance uniform polishing results
- high surface quality
- sands faster than conventional abrasives
- extremely long life span

(not suitable for intermediate varnish sanding)







Janser GmbH Machines, specialist tools, work clothing

F-mail· info@janser.com Internet: www.janser.com

Böblinger Straße 91 71139 Ehningen **GFRMANY** 

Phone +49 / 7034 / 127-0 Fax +49 / 7034 / 8838



# FIBERPAD

## Refining mat

Structured, natural parquet surfaces are enjoying great popularity!

...we show you how it works.



The advantage for your customers: the treated surface has a higher quality and is less delicate

Prerequisites: factory pre-sanded parquet flooring or prepared/pre-sanded in situ

#### **FIBERPAD**

The unique FIBREPAD has only recently been developed for fine sanding of parquet flooring and for deep cleaning of surfaces like wood, stone and metal.

Its extremely long life span means that the pad doesn't need to be changed in the middle of the work process.

The advantage is an even polishing result.

Order-no. 488 812 000 Ø 406



### Pad mounting plate PIN-LOCK

Together with the FIBERPAD the newly developed pad mounting plate PIN-LOCK is recommended.

The fine bristles attach themselves firmly onto the pad which gives it a totally firm fit while working. Suitable for all other pads as well.

Order-no.	783 000 410	$\varnothing$ 375 without distance ring
Order-no.	783 000 420	Ø 375 with distance ring
Order-no.	783 000 430	Ø 406 with distance ring

PIN-LOCK replacement disc

**Order-no. 783 000 415** Ø 375

Order-no. 783 000 435 Ø 40





#### Janser GmbH

Machines, specialist tools, work clothing

E-mail: info@janser.com Internet: www.janser.com Böblinger Straße 91 71139 Ehningen GERMANY Phone +49 / 7034 / 127-0 Fax +49 / 7034 / 8838

