





The OXI Sand technology provides longer lifetime and less dust for the sanding process

The innovative abrasive for parquet sanding

The innovative manufacturing process of the OXI Sand abrasives enables precise application of the abrasive grains and thus ensures the best possible removal of sanding dust. In addition, the new, innovative non-stick

coating causes that the OXI Sand sandpaper is significantly less clogged. In combination with the high-quality abrasive grain, a lifetime up to 30% longer is possible, as well as an optimal, homogeneous sanding surface.

Janser's OXI Sand is a perfect match for our Columbus or Speedtronic machines with TRIVO-DISC II, as well as the RS-150 and DEOS, and offers a complete range for high-quality sanding results for surfaces, edges and corners.



OXISand

High sanding performance - whether round or square

SPECIAL FEATURES:

Longer lifetime

The precise application of the abrasive grains creates transport channels to transport the sanding dust away. This results in a more consistent sanding performance and less dust.

Sanding with less dust

Effective multi-hole perforation for optimal suction and perfect sanding.



Less clogging

The innovative new coating enables better dust repellency (non-stick coating).

Homogenous sanding pattern

Thanks to the new, flexible carrier material, OXI Sand adapts perfectly to the parquet surface.

Available in five different grits





	Ø 150 mm (PU)	70x200 mm (PU)
Grit 40	448 107 040 (50)	448 110 040 (50)
Grit 60	448 107 060 (50)	448 110 060 (50)
Grit 80	448 107 080 (100)	448 110 080 (50)
Grit 100	448 107 100 (100)	448 110 100 (50)
Grit 120	448 107 120 (100)	448 110 120 (50)

More information please find here







The right machine for each application

Sanding in corners with the DEOS orbital sander

This small and light sander is equipped with a brushless motor and is particularly suitable for corner sanding.

Comes in transport case complete with protective pad, soft pad, circular pad, each with 50 pieces of sandpaper OXI Sand 70 x 200 Kö 60, 80, 100

Order no. 448 110 600



Edge sanding with the parquet edge sander RS 150

The RS 150 impresses with its high removal rates and enormous maneuverability when sanding the edges of parquet.

Comes complete with 5 mm soft pad and 2 m suction hose (without carrying case)

Order no. 454 500 000



Transport case without content

Order no. 452 500 900









Surface sanding with the triple disc plate TRIVO-DISC

The future of fine sanding of parquet surfaces with the innovative self-propelled TRIVO-DISC II from Janser





suitable for Columbus Mod.145 SH, 155 S and Speedtronic

TRIVO-DISC II in case

fully equipped with:

25 x Velcro sanding discs ceramic grit 36

50 x Velcro sanding discs ceramic grit 60

50 x Velcro sanding discs OXI Sand grit 60

50 x Velcro sanding discs OXI Sand grit 80

50 x Velcro sanding discs OXI Sand grit 100

3 x FIBERPAD Ø 150mm

3 x Soft pads 5mm

Order no. 112 882 900

NEW With OXISand



TRIVO-DISC II in Systainer

fully equipped with: trial set of abrasives, 3 x FIBERPAD Ø 150mm

3 x Soft pads 5mm



Order no. 112 882 700



If you would like to find out more about Janser and our product range, you will find it here.

If you have any questions, please contact us





